POLYURETHANE TUBING



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:17 PM

SKU
: 34

BRAND
: DIXON VALVE

MODEL
: 04063

Use:
Designed for use with push-in fittings

Features:
Excellent memory, flexibility and resistance to kinking
Good resistance to fuels and oils
Low gas and vapor permeability
High compressive strength
Low compressive set and extractability levels
Outstanding abrasion resistance
UV stabilized

Construction:
Naturally transparent
Glossy finish

Note:
NSF61 certified for potable water

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	04063
Material	Polyurethane
Temperature Range	-40°F to 165°F (-40°C to 74°C)
Tube ID	.062"
Tube OD	1/8"
Wall Thickness	.0295
Weight Lb	0.3750
Working Pressure	255 PSI at 75°F (24°C)

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us