NYLON TUBING

DATE
: 11/23/2026 07:41 PM



SKU
: 39

BRAND
: DIXON VALVE

MODEL
: 05106

** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Use:
Recommended for applications requiring low density, lightweight toughness, flexibility and chemical resistance
Designed for use with push-in fittings

Features:
Packaged in plastic bags
UV stabilized

Construction:
Naturally transparent
Glossy finish

Note:
NSF61 certified for potable water

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	05106
Material	Nylon
Temperature Range	-40°F to 180°F (-40°C to 82°C)
Tube ID	.106"
Tube OD	5/32"
Wall Thickness	.025
Weight Lb	0.3940

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Working Pressure	350 PSI at 75°F (24°C)

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us