# POLYETHYLENE NATURAL TUBING




** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:04 PM

SKU
: 478

BRAND
: DIXON VALVE

MODEL
: 1208

Applications:
Designed for FDA applications

Use:
Designed for use with push-in fittings
For use with plastic or metal inserts with outer sleeve; ferrule or clamps

Specifications:
Complies with 21CFR 177.1520 (c) food contact

Features:
UV stabilized

Construction:
Natural
Flexible, lightweight, low-density polyethylene (LLDPE) tubing
Glossy finish

Note:
NSF61 certified for potable water

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Factory Part Number** | 1208 |
| **Material** | Polyethylene |
| **Temperature Range** | -50°F to 140°F (-46°C to 60°C) |
| **Tube ID** | .250" |
| **Tube OD** | 3/8" |
| **Wall Thickness** | .062 |
| **Weight Lb** | 2.3000 |
| **Working Pressure** | 150 PSI at 75°F (24°C) |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us