ASME AIR TANK RECEIVER MANIFOLD ASSEMBLY WITH AIR KING COUPLERS



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 01:03 AM

SKU
: 482

BRAND
: DIXON VALVE

MODEL
: 1217AR-4AK

Appliations:
Safely distributes compressed air to machines and tools.

Service:
• 7 gallon capacity provides air reserve needed for operation of tools
• 200 PSI maximum working pressure for tank (Working pressure of the system
is limited to maximum working pressure of the components, i.e. 150 PSI for Air King)

Features:
• All tank outlets have female NPT threads
• Portable - easy carry handles standard
• Solid base with mounting holes standard
• Approximate tank dimensions are 12" x 17"; 40" x 24" with frame
• Painted safety orange

Components:
• Spring-loaded safety shut-off valves (cut-off flow rate 160-180 CFM at 90 PSI)
• Safety pop-off valve (200 PSI) to protect against over-pressurizing of tank
• 0-300 PSI gauge
• Locking handle ball valves
• Drain valve provides for removal of accumulated oil and water

Codes and Standards:
• Built to ASME Code, National Board registered
• Conforms to OSHA Standards 1910.169 and 1926.306

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Brand	DIXON Valve
Factory Part Number	1217AR-4AK
Material	Steel
Capacity	7 gallons
Working Pressure	200 PSI
Weight Lb	92.0000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us