NON-COLLAPSIBLE FIRE AND UTILITY HOSE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:27 PM

SKU
: 1464

BRAND
: DIXON VALVE

MODEL
: 15B15-50RAF

Construction:
Outer construction is designed to withstand abrasion
Coupled with female and male NST (NH) thread, rocker lug, aluminum expansion ring couplings

Available Options:
Consult Dixon™ for pricing and availability of other lengths, threads and configurations.
Also available with chrome brass fittings

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Bowl Size	1-1/2"
Burst Pressure	600 PSI at ambient temperature 70°F (21°C)
Color	Red
Coupling Type	Aluminum Expansion Ring, Rocker Lug
Factory Part Number	15B15-50RAF
Hose Size	1-1/2"
Thread	NST (NH)
Weight Lb	48.0000
Working Pressure	200 PSI at ambient temperature 70°F (21°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us