POLYURETHANE TUBING



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:07 PM

SKU
: 1609

BRAND
: DIXON VALVE

MODEL
: 16320

Use:
Designed for use with push-in fittings

Features:
Excellent memory, flexibility and resistance to kinking
UV stabilized

Construction:
Naturally transparent
Glossy finish

Note:
NSF61 certified for potable water

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	16320
Material	Polyurethane
Optional Pkg/Box Qty	1
Temperature Range	-40°F to 165°F (-40°C to 74°C)
Tube ID	.320"
Tube OD	1/2"
Wall Thickness	.0900
Weight Lb	2.9200

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Working Pressure	175 PSI at 75°F (24°C)

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us