DIXON® CAM & GROOVE TYPE D COUPLER X FEMALE NPT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:44 PM

SKU
: 2609

BRAND
: DIXON VALVE

MODEL
: 250-D-BR

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:
Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Features:
Precision machined to rigid tolerances
Stainless pins will not rust or bind, providing great strength and safety
Recess holds gasket firmly in place- ensures proper placement
Long shank design allows proper banding, thus eliminating the major cause of hose damage

Construction:
Buna-N gasket
Durable stainless steel cam arm pins

Available Options:
Other gasket types are available, contact Dixon.

How it works:
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Note:
Parts are manufactured in Canada, replacement handle: Part # CARP12BZ

Safety notes:

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	250-D-BR
Material	Brass
Maximum Operating Pressure	150 PSI
Seal	Buna-N
Size	2-1/2"
Weight Lb	3.1000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us