# FEMALE NPSM SWIVEL X PUSH-ON HOSE BARB BALL SEAT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 02:13 AM

SKU
: 2858

BRAND
: DIXON VALVE

MODEL
: 2781212CBC

Specifications:
Number of Barbs: 3
Barb Length: 1.50"

Construction:
Ball seat type

Installation
Assembly Instructions:
1. Trim hose end with smooth square cut.
2. Lubricate either push-on fitting, hose or both.
3. Insert push-on fitting into hose until first barb is in hose.
4. Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from end. Push with a steady force until end of hose is covered by yellow plastic cap.

Instructions
Disassembly instructions:
1. Leaving push-on fitting in place, make a 1" cut in the hose along the barbed end of the fitting. Note: Be careful not to nick barbs when cutting the hose.
2. With firm grip on hose, give a sharp downward pull to release the fitting from the hose.

Note:
No hose clamps or ferrules are needed

Safety notes:
Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.
Caution: Push-on fittings will properly grip push-on hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

cap.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Factory Part Number** | 2781212CBC |
| **Component Material** | Brass Cap |
| **Weight Lb** | 0.2220 |
| **Female Thread** | NPSM |
| **Female Thread Size** | 3/4"-14 |
| **Hex** | 1-3/16" |
| **Hose ID** | 3/4" |
| **Length** | 2.36" |
| **Material** | Brass |
| **Pressure Rating** | 350 PSI |
| **Temperature Range** | -40°F to 150°F |



KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us