FEMALE NPSM SWIVEL X PUSH-ON HOSE BARB GASKET SEAT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 01:40 AM

SKU
: 2869

BRAND
: DIXON VALVE

MODEL
: 2800608CBC

Specifications:
Number of Barbs: 2
Barb Length:.92"

Construction:
Gasket seat type

Installation
Assembly Instructions:
1. Trim hose end with smooth square cut.
2. Lubricate either push-on fitting, hose or both.
3. Insert push-on fitting into hose until first barb is in hose.
4. Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from end. Push with a steady force until end of hose is covered by yellow plastic cap.

Instructions
Disassembly instructions:
1. Leaving push-on fitting in place, make a 1" cut in the hose along the barbed end of the fitting. Note: Be careful not to nick barbs when cutting the hose.
2. With firm grip on hose, give a sharp downward pull to release the fitting from the hose.

Note:
No hose clamps or ferrules are needed
280 Series is not recommended for water due to fiber gasket- for air service only.

Safety notes:
Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Caution: Push-on fittings will properly grip push-on hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	2800608CBC
Component Material	Brass Cap
Weight Lb	0.0970
Female Thread	NPSM
Female Thread Size	1/2"-14
Hex	15/16"
Hose ID	3/8"
Length	1.80"
Material	Brass
Pressure Rating	350 PSI
Temperature Rating	-40 to +150°F

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us