FEMALE 45° SAE SWIVEL X PUSH-ON 90° ELBOW



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:47 PM

SKU
: 2935

BRAND
: DIXON VALVE

MODEL
: 2890610CSAE

Specifications:
2 barbs

Features:
Notch in nut for SAE identification

Installation
Trim hose end with a smooth square cut.
Lubricate either Lok-On fitting, hose or both.
Insert Lok-on fitting into hose until first barb is in the hose.
Place end of fitting against a flat object (bench, wall, etc.) and grip the hose one inch from the end. Push with a steady force until the end of the hose is covered by the yellow plastic cap.

Note:
No hose clamps or ferrules are needed

Safety notes:
Dixon push-on fittings are intended for use with Lok-On (push-on style) hose only.
Lok-On fittings will properly grip Lok-On hose only when pushed all the way in, with the cut end of the hose completely concealed by the plastic cap.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	2890610CSAE
Component Material	Yellow Plastic Cap
Weight Lb	0.1100
Female Thread	UNF
Female Thread Size	5/8"-18
Hose ID	3/8"
Material	Plated Steel
Pressure Rating	350 PSI
Temperature Range	-40 to +150°F
Tube OD	3/8"

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us