DQC CM-SERIES INDUSTRIAL MOLD INTERCHANGE VALVED COUPLER PUSH-LOC BARB





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:25 PM

SKU
: 3035

BRAND
: DIXON VALVE

MODEL
: 2CMB2-B

Specifications:
Rated pressure for connected Brass Valved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 6,000 PSI (400 bar) Burst

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Silicone gaskets and valve O-rings are standard

Compatibility & Interchange Data:
Mold Coolant Interchange
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:
Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Factory Part Number	2CMB2-B
Hose ID	1/4"
Length	2.64"
Material	Brass
Maximum OD	0.69"

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Temperature Range	-90°F to +400°F (-68°C to +205°C)
Weight Lb	0.1000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us