# DQC CM-SERIES INDUSTRIAL MOLD INTERCHANGE UNVALVED COUPLER PUSH-LOC BARB

DATE
: 11/23/2026 10:58 PM

SKU
: 3038



BRAND
: DIXON VALVE

MODEL
: 2CMB3-B-E



Specifications:
Rated pressure for connected Brass Unvalved Coupler and Brass Plug: 300 PSI (20 bar) Maximum Working and 10,000 PSI (700 bar) Burst
Rated pressure for connected Brass Unvalved Coupler and Steel Plug: 500 PSI (35 bar) Maximum Working and 10,700 PSI (750 bar) Burst

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Silicone gaskets are standard

Compatibility & Interchange Data:
Mold Coolant Interchange
Foster Series- FJT, Hansen Flo-Temp, Tomco MC-Series, Parker Moldmate, DME Jiffy-Tite

Safety notes:
Maximum working and burst pressure is based on a coupled set, contact Dixon for pressure ratings.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Body Size** | 1/4" |
| **Factory Part Number** | 2CMB3-B-E |
| **Hose ID** | 3/8" |
| **Length** | 2.08" |
| **Material** | Brass |
| **Maximum OD** | 0.69" |
| **Temperature Range** | -90°F to +400°F (-68°C to +205°C) |
| **Weight Lb** | 0.1100 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us