DQC E-SERIES STRAIGHT THROUGH INTERCHANGE HOSE BARB COUPLER





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:16 PM

SKU
: 22269

BRAND
: DIXON VALVE

MODEL
: 2ES2-B

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings
These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using solid brass
Nitrile (Buna-N) seals are standard

Available Options:
Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
Operating pressures for the standard hose barbs utilizing hose barb end connections may be dramatically reduced to that of the hose rating and/or hose and end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Burst Pressure	20,800 PSI (1,434 Bar)
Factory Part Number	2ES2-B
Hose ID	1/4"
Length	2.06" (52.2mm)
Material	Brass
Maximum OD	1" (25.4mm)
Maximum Operating Pressure	5,200 PSI (359 Bar)
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Weight Lb	0.1600

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us