
DIXON CAM & GROOVE TYPE C COUPLER X HOSE SHANK





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:10 PM

SKU
: 26977

BRAND
: DIXON VALVE

MODEL
: 300-C-MI

Applications:
Designed for use with liquids, consult Dixon for specific recommendations
Use:
Suitable for use with King Crimp™ sleeves and ferrules
Specifications:
Produced to interchange with all product produced to Commercial Item Description A-A-59326D
Features:
Precision machined to rigid tolerances
Stainless pins will not rust or bind, providing great strength and safety
Recess holds gasket firmly in place- ensures proper placement
Long shank design allows proper banding, thus eliminating the major cause of hose damage
Construction:
Buna-N gasket
Durable stainless steel cam arm pins
Supplied with safety clips
Available Options:
Other gasket types are available, contact Dixon.
How it works:
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.
Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!
Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Material	Unplated Ductile Iron
Maximum Operating Pressure	125 PSI, 150 PSI with King Crimp Ferrule system
Factory Part Number	300-C-MI
Seal	Buna-N
Size	3"
Weight Lb	4.0700

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us