BAYCO HIGH FLOW SERIES SWING CHECK VALVE FEMALE NPT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 01:14 AM

SKU
: 3502

BRAND
: DIXON VALVE

MODEL
: 3030TE-SSP

Applications:
Often used on both the blower and trailer, designed to prevent product backflow if a product line should become plugged.

Use:
When in use the flapper can swing completely out of the air path, resulting in increased air flow and subsequently increased product flow.
Complete repairs can easily be carried out on all high flow swing check valves without removing from the tank.

Features:
Flapper return springs are standard
Huck bolted flapper assembly prevents loose parts from contaminating the product.

Construction:
Aluminum body and inspection lid
Stainless steel hardware
All white EPDM & silicone seals are compliant with FDA

Safety notes:
Inspection lids can be removed to facilitate routine flapper assembly inspections (system must not be in service during inspections or repair.)
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Female Thread	NPT
Female Thread Size	3"
Includes	Flapper return springs
Length	7-1/8"
Material	Aluminum
Factory Part Number	3030TE-SSP
Seal	White silicone
Temperature Rating	400°F (204°C)
Weight Lb	5.1000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us