TYPE AA ADAPTER X ADAPTER

DATE
: 11/23/2026 09:37 PM

SKU
: 3517

BRAND
: DIXON VALVE

MODEL
: 3040-AA-SS



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:
Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Construction:
Produced as a welded fabrication

How it works:
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!
Pressure rating is based on the seal of the mating part
Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F / 21°C with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Material	316 Stainless Steel
Maximum Operating Pressure	100 PSI
Factory Part Number	3040-AA-SS
Size	3" x 4" (75mm x 100mm)
Weight Lb	5.9000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us