BLOWER MOUNTED SWING CHECK VALVE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:10 PM

SKU
: 3553

BRAND
: DIXON VALVE

MODEL
: 3090MB

Applications:
Designed specifically for use on tractor mounted air blowers and to replace the multiple pipe connections typically used to connect the blower to a swing check and air relief valve.

Use:
Fastens directly to blower using available TTMA thread adapters

Features:
Manufactured with a 4" TTMA flange connection for fastening directly to the blower
2" NPT port for air relief valve
Interchangeable inlet / outlet ports
Interchangeable inlet / outlet ports

Construction:
Aluminum body
White silicone spring loaded flapper
Stainless steel hardware
Silicone lid seal
Compact unit includes high flow swing check, port for air relief valve and inlet / outlet ports
All white silicone seals are compliant with FDA

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Component Material	White silicone flapper
Length	12-1/2"
Material	Aluminum
Maximum Temperature	400°F (204°C)
Outlet	4" Cam & Groove Adapter
Factory Part Number	3090MB
Weight Lb	7.5210

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us