METRIC PUSH-IN MALE CONNECTOR M5



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:11 PM

SKU
: 3567

BRAND
: DIXON VALVE

MODEL
: 31010619

Use:
Compatible tubing: semi-rigid nylon, polyurethane and polyethylene tube
Vacuum capability: vacuum of 28" Hg (99% vacuum)

Features:
Positive seal: sealing and holding is accomplished instantaneously
Reusable: connect and disconnect numerous times
Full flow: fitting seals on outside diameter of tubing
Internal hex allows ease of assembly in tight places

Construction:
Polypropylene release button
Nickel-plated brass threads
Silicone free

Installation
Quick connect and disconnect, no tools required
To connect, simply push tubing in.
To disconnect, press the release ring towards the fitting and pull tubing out.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	31010619
Male Thread	M5
Material	Nickel Plated Brass
Pressure Rating	290 PSI at 70°F (21°C)
Seal	Buna-N D-seal
Temperature Range	-4°F to 175°F (-20°C to 79°C)
Tube OD	6 mm
Weight Lb	0.0110

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us