STEEL 3500 NIPPLE WITH FERRULE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:36 PM

SKU
: 22387

BRAND
: DIXON VALVE

MODEL
: 3509WF

Use:
The constant vibration created by air tools, like air drills and pavement breakers, is destructive to air hose couplings, especially the quick-acting type. To provide protection against coupling breakage and related hazards, Dixon recommends the use of a whip hose.
To construct a whip hose, connect one end of a short (3' to 10') air hose to the air tool using a 3500 type steel nipple. Connect the other end of the hose to the air supply using the standard quick-acting coupling. The heat treated 3500 nipple will withstand vibration far better than the standard coupling and provide a safer connection. The whip hose should remain permanently connected to the tool.

Features:
Low profile
Streamline appearance

Construction:
Zinc plated steel 3500 nipple
Carbon steel ferrule

Installation
Can be crimped or swaged-on to achieve maximum coupling sealing and retention

Note:
For crimp or swage recommendations, contact Dixon.

Safety notes:
For air and water service only
To provide protection against coupling breakage and related hazards, Dixon® recommends the use of a whip hose.

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	3509WF
Hose OD From	54/64"
Hose OD To	58/64"
Hose Size	1/2"
Male Thread	NPT
Male Thread Size	1/4"
Material	Steel
Pressure Rating	600 PSI at 70°F (21°C)
Weight Lb	0.2800

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us