NICKEL-PLATED BRASS LEGRIS PUSH-IN EQUAL UNION TEE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:35 PM

SKU
: 3876

BRAND
: DIXON VALVE

MODEL
: 36040400

Applications:
Applications include: food industry, packaging, robotics, pulp and paper and wash down
Push-to-connect forged fittings are nickel plated and have an FKM seal making them suitable to use with liquids and gaseous fluids. Fittings are plated with a high phosphorous FDA nickel plate allowing them to be used in applications where exposure to harsh environments is present.

Features:
Full flow
Excellent resistance to abrasion and corrosion
Silicone free

Construction:
Body: High phosphorous FDA nickel plated brass
Back-up washer: High phosphorous FDA nickel plated brass
Collet: High phosphorous FDA nickel plated brass
O-ring: FKM fluoroelastomer conforming to FDA standards
Base: High phosphorous FDA nickel plated brass

Available Options:
Available in fractional and metric sizes, contact Dixon™ for more information

Safety notes:
Maximum circuit pressure depends on media, temperature and diameter of tube used
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	36040400
Material	Nickel-Plated Brass
Maximum Operating Pressure	435 PSI
Seal	FKM
Temperature Range	-4°F to 302°F (-20°C to 150°C)
Tube OD	5/32"
Vacuum Capability	28" HG
Weight Lb	0.0100

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us