NICKEL-PLATED BRASS LEGRIS PUSH-IN MALE ELBOW



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 01:02 AM

SKU
: 3886

BRAND
: DIXON VALVE

MODEL
: 36095611

Applications:
Applications include: food industry, packaging, robotics, pulp and paper and wash down
Push-to-connect forged fittings are nickel plated and have an FKM seal making them suitable to use with liquids and gaseous fluids. Fittings are plated with a high phosphorous FDA nickel plate allowing them to be used in applications where exposure to harsh environments is present.

Specifications:
FDA compliant

Features:
Full flow
Excellent resistance to abrasion and corrosion
Silicone free
Body is orientable for positioning purposes

Construction:
Body: High phosphorous FDA nickel plated brass
Back-up washer: High phosphorous FDA nickel plated brass
Collet: High phosphorous FDA nickel plated brass
O-ring: FKM fluoroelastomer conforming to FDA standards
Base: High phosphorous FDA nickel plated brass
Thread sealant is intentionally left off product so the appropriate sealant for the application can be applied

Available Options:
Available in fractional and metric sizes, contact Dixon™ for more information

Safety notes:
Maximum circuit pressure depends on media, temperature and diameter of

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

tube used

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	36095611
Male Thread	NPT
Male Thread Size	1/8"
Material	Nickel-Plated Brass
Maximum Operating Pressure	435 PSI
Seal	FKM
Temperature Range	-4°F to 302°F (-20°C to 150°C)
Tube OD	1/4"
Vacuum Capability	28" HG
Weight Lb	0.1500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us