LEGRIS STAINLESS STEEL PUSH-IN MALE CONNECTOR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 02:12 AM

SKU
: 3988

BRAND
: DIXON VALVE

MODEL
: 38055611

Applications:
Suitable for many industries such as: chemical, food, packaging and medical

Use:
Compatible with a range of tubes including: semi-rigid nylon tube, flexible polyurethane tube, low density polyethylene, PTFE tube FEP 140, stainless steel and copper tube (when grooved)

Specifications:
Materials conforming to FDA and 1934/2004 CE standards

Features:
Internal hex allows ease of assembly in tight places

Construction:
AISI 316 stainless steel body with 316L stainless steel backup washer and 303L stainless steel collet
Silicone free
FKM O-ring

Note:
Thread sealant does not come pre-applied on male threads, allowing the appropriate sealant for the application to be applied by the user.

Safety notes:
Maximum circuit pressure depends equally on the type and diameter of the tube used.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	38055611
Male Thread	NPT
Male Thread Size	1/8"
Material	Stainless Steel
Maximum Operating Pressure	290 PSI
Seal	FKM O-ring
Temperature Range	-4°F to 245°F (-20°C to 118°C)
Tube OD	1/4"
Vacuum Capability	28" HG
Weight Lb	0.0250

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us