DQC K-SERIES ISO-A INTERCHANGE FEMALE COUPLER





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 09:26 PM

SKU
: 22454

BRAND
: DIXON VALVE

MODEL
: 3KF3

Features:
Poppet style shut-off valve

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Steel coupler sleeves are hardened to resist deformation and maximize service life.
Nitrile (Buna-N) seals are standard
Couplers have a PTFE Anti-Extrusion ring.
Valve seals are crimped in place to maintain integrity during excessive flow conditions and pressurized connection.

Available Options:
Contact Dixon for all available option adders
Standard seal options include: FKM, EPDM, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone
Kalrez® seal options include: 4079, 6375 and 7075
Valve options include: Unvalved, actuator, steel, brass, 303 stainless steel and 316 stainless steel
Locking sleeve option available
Oxy-Clean treatment is available

Compatibility & Interchange Data:
Interchangeable to ISO7241 Series 'A'
Parker 6600-Series, Aeroquip/Eaton FD56 (5600)
Faster ANV, Hansen HA 15000, Safeway S56-Series

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Burst Pressure	18270 PSI (1200 bar)
Factory Part Number	3KF3
Hex	7/8"
Length	2.23" (56.6mm)
Material	Steel
Maximum OD	1.19" (30.2mm)
Maximum Operating Pressure	4000 PSI (275 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female NPTF
Thread Size	3/8"-18
Weight Lb	0.3700

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us