M-SERIES ARO PNEUMATIC AUTOMATIC MALE THREADED COUPLER





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 07:11 PM

SKU
: 4112

BRAND
: DIXON VALVE

MODEL
: 3MM3-PL

Specifications:
Rated pressure for connected Steel Coupler & Steel Plug: 300 PSI (20 bar) Maximum Working and 3,300 PSI (228 bar) Burst

Construction:
Machined components are manufactured using solid bar stock.
Stainless steel springs. Carbon steel balls and retaining rings.
Nitrile (Buna-N) seals are standard
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
ARO 310
Hansen 210/310

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Factory Part Number	3MM3-PL
Hex	1-1/16"
Length	1.89"
Material	Nickel Plated Brass Body, Steel Sleeve
Maximum OD	1.26"
Pressure Rating	See Product Details
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPT
Thread Size	3/8"
Weight Lb	0.3800

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us