SANITARY PRESSURE GAUGE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:14 AM

SKU
: 4119

BRAND
: DIXON VALVE

MODEL
: 3S-C-15U-GFBTSS

Specifications:
Accuracy: ± 1.5% of full scale
Over range capacity: 30%
3-1/2" dial

Features:
Rezero feature: standard on pointer

Construction:
Wetted surfaces: 316L stainless steel
Surface finishes (wetted parts): Ra max = 25 micro inches
Lens material: polycarbonate
Standard fill: food grade glycerin
Case material: 304 stainless steel

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Case	Glycerin Filled
Fitting Type	Clamp
Material	316L Stainless Steel
Mount	Bottom
Factory Part Number	3S-C-15U-GFBTSS
Pressure Range	0-60 PSI
Size	1-1/2"
Temperature Range	0°F to 250°F (-18°C to 121°C)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Weight Lb	3.0000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us