CAM & GROOVE ADAPTER BUTT WELD TO SCHEDULE 40 PIPE/SOCKET WELD TO NOMINAL TUBING

DATE
: 11/24/2026 10:17 PM

SKU
: 4321

BRAND
: DIXON VALVE

MODEL
: 400AWBPSTAL





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:
Produced to interchange with all product produced to Commercial Item Description A-A-59326D

Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!
Final weld preparation, as with all weld fittings, is the responsibility of the welder.
Line drawings are for reference only. Consult Dixon for specific dimensions.
Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F (21°C) with a standard Buna-N seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Material	356T6 Aluminum
Maximum Operating Pressure	100 PSI
Factory Part Number	400AWBPSTAL
Size	4"
Weight Lb	1.2000

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us