HEAVY DUTY BUTTERFLY VALVE

DATE
: 11/23/2026 08:53 PM

SKU
: 27149



BRAND
: DIXON VALVE

MODEL
: 4BF416DITF-CNBR

** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Low-pressure transfer of water, acids, chemicals, slurries, and other liquids
Designed for all low-pressure hydraulic fracturing applications
Features:
Locator notches around the outer edge of the body allow the valve to easily line up at center
Actuator mounting flange outfitted with both industry standard and ISO bolt circle diameters
Thicker stems deliver a more durable and reliable performance
Grease zerk added to body neck for reliable performance
10-position throttling handle for controlled accuracy
For use between lightweight flanges: 125 lb., 150 lb., or butterfly valve flange
Valve is rebuildable, contact Dixon for replacement parts
Note:
Dixon provides actuation services for industrial and sanitary valves.
Halliburton SAP# 100001149
Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Description	Valve with Buna-N seat
Material	Body: ductile iron, Disc: nickel-plated ductile iron , Bushings: PTFE, O-rings: Buna-N, Stems: 416 stainless steel, Retaining pins: stainless steel, Handle: malleable iron
Maximum Operating Pressure	200 PSI

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	4BF416DITF-CNBR
Seat	Buna-N or FKM
Size	4"
Temperature Range	Buna-N seat -20°F to 200°F , FKM seat 0°F to 200°F (Buna-N seat -28°C to 93°C, FKM seat -17°C to 93°C)

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us