
DQC CVV-SERIES EUROPEAN INTERCHANGE FEMALE COUPLER





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:38 PM

SKU
: 4879

BRAND
: DIXON VALVE

MODEL
: 4CVVBF4

Construction:
Machined components are manufactured using solid bar stock
Steel retaining rings and springs maximize service life in rugged environments.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:
European Screw-Together Interchange
Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	23200 PSI (1600 Bar)
Factory Part Number	4CVVBF4
Hex	27mm
Length	2.66" (67.5mm)
Material	Steel
Maximum OD	1.65" (41.8mm)
Maximum Operating Pressure	5800 PSI (400 Bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female BSPP

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Thread Size	1/2"-14
Weight Lb	0.6000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us