DQC CVV-SERIES EUROPEAN INTERCHANGE FEMALE COUPLER





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:57 AM

SKU
: 4882

BRAND
: DIXON VALVE

MODEL
: 4CVVFM1815

Construction:
Machined components are manufactured using solid bar stock
Steel retaining rings and springs maximize service life in rugged environments.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Nitrile (Buna-N) seals are standard

Compatibility & Interchange Data:
European Screw-Together Interchange
Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS, Stucchi VD Series

Note:
Threaded sleeves enable easy connection and disconnection while system is under residual pressure only.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	23200 PSI (1600 Bar)
Factory Part Number	4CVVFM1815
Hex	27mm
Length	2.66" (67.5mm)
Material	Steel
Maximum OD	1.65" (41.8mm)

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Maximum Operating Pressure	5800 PSI (400 Bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female Metric
Thread Size	M18X1.5

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us