DQC EA-SERIES WATER-BLAST INTERCHANGE COUPLER





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 05:19 PM

SKU
: 4898

BRAND
: DIXON VALVE

MODEL
: 4EAF3

Construction:
Machined components are manufactured using solid high strength steel bar stock.
Stainless steel retaining rings and springs maximize corrosion resistance and extend service life.
Latches are manufactured from high-strength steel and plated with electroless nickel.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Nitrile (Buna-N) seals are standard
Couplers have a PTFE Anti-Extrusion ring to prevent O-Ring dynamic impulse pressure damage

Available Options:
Contact Dixon for all available option adders
Standard seal options include: FKM, EPDM, FDA FKM, Mil-Nitrile and Silicone
Kalrez® seal options include: 4079, 6375 and 7075

Compatibility & Interchange Data:
Water-Blast Interchange
Parker Series-WB, Aeroquip FD69, Snap-Tite 56-Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	30000 PSI
Factory Part Number	4EAF3
Hex	1-1/4"
Length	2.20"
Material	Steel
Maximum OD	1.62"
Maximum Operating Pressure	10000 PSI
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female NPTF
Thread Size	3/8"-18
Weight Lb	0.6800

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us