DQC E-SERIES STRAIGHT THROUGH INTERCHANGE FEMALE COUPLER WITH LOCKING SLEEVE





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:45 PM

SKU
: 4903

BRAND
: DIXON VALVE

MODEL
: 4EF4-S-LS

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings
These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using 303 stainless steel bar stock
Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.
Nitrile (Buna-N) seals are standard

Available Options:
Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	12,000 PSI (827 Bar)
Factory Part Number	4EF4-S-LS
Female Thread	NPTF
Female Thread Size	1/2"-14
Hex	1-1/8"
Length	1.86 (47.2mm)
Material	303 Stainless Steel
Maximum OD	1.34 (34.0mm)
Maximum Operating Pressure	3,000 PSI (207 Bar)
Seal	Buna-N
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Weight Lb	0.3500

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us