DQC E-SERIES STRAIGHT THROUGH INTERCHANGE MALE COUPLER





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:36 PM

SKU
: 4904

BRAND
: DIXON VALVE

MODEL
: 4EM4-B

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings
These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using solid brass
Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.
Nitrile (Buna-N) seals are standard

Available Options:
Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	8,800 PSI (607 Bar)
Factory Part Number	4EM4-B
Male Thread	NPTF
Male Thread Size	1/2"-14
Material	Brass
Maximum Operating Pressure	2,200 PSI (152 Bar)
Temperature Range	-40°F - +250°F (-40°C - +121°C)
Weight Lb	0.3600

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us