
DUAL-LOCK P-SERIES THOR INTERCHANGE COUPLER WITH FERRULE

DATE
: 11/23/2026 07:45 PM

SKU
: 22682

BRAND
: DIXON VALVE

MODEL
: 4PS4-WF



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Construction:
Machined components are manufactured using solid steel bar stock
Stainless steel retaining ring and spring maximize corrosion resistance and extend service life
Steel componentry is plated using ROHS Compliant Trivalent Chrome
Steel couplings have a zinc cast sleeve
Nitrile (Buna-N) seals standard, temperature range-40°F to 250°F (-40°C to 121°C)

Available Options:
3/8" and 1" sizes available upon request, contact Dixon®

Compatibility & Interchange Data:
Thor Finger-Lock Interchange
Interchanges with Thor PHC-series, National Series 'A' and Campbell Double-Lock

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Factory Part Number	4PS4-WF
Hose ID	1/2"
Hose OD From	54/64"
Hose OD To	1-2/64"
Material	Trivalent Chrome Plated Steel

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Weight Lb	0.6300
Working Pressure	300 PSI at ambient temperature 70°F (21°C)

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us