# DUAL-LOCK P-SERIES THOR INTERCHANGE HOSE BARB COUPLER WITH KNURLED FLANGED SLEEVE

DATE
: 11/23/2026 11:44 PM

SKU
: 4971

BRAND
: DIXON VALVE

MODEL
: 4PS6-FS





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Construction:
Machined components are manufactured using solid bar stock.
Nitrile (Buna-N) seals standard
Stainless steel retaining ring and spring maximize corrosion resistance and extend service life on the 1 piece sleeve. 2-Piece Sleeve has a phosphor bronze spring.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
Thor Finger-Lock Interchange
Interchanges with National A type, Campbell Double-Lock and Thor PHC series couplings

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Body Size** | 1/2" |
| **Factory Part Number** | 4PS6-FS |
| **Hose ID** | 3/4" |
| **Material** | Steel |
| **Maximum Operating Pressure** | 300 PSI (20 bar) |
| **Temperature Range** | -40°F to +250°F (-40°C to +121°C) |
| **Weight Lb** | 0.6500 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us