
SHD-SERIES SCHRADER PNEUMATIC FEMALE THREADED COUPLER





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:31 PM

SKU
: 4983

BRAND
: DIXON VALVE

MODEL
: 4SHDF6

Construction:
Machined components are manufactured using solid bar stock.
Stainless steel toggle-pawls and springs. Carbon steel retaining rings.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
Adapter components are constructed of brass.
Sleeves are constructed of steel.
Nitrile (Buna-N) seals standard

Compatibility & Interchange Data:
Schrader Twist-Lock Interchange
Parker Twist-Lock, Tomco Series-TL, Foster SHD

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	13400 PSI (924 bar)
Factory Part Number	4SHDF6
Hex	1-1/8"
Length	2.81"
Material	Aluminum
Maximum OD	1.50"
Maximum Operating Pressure	300 PSI (20 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPT
Thread Size	3/4"
Weight Lb	0.4400

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us