TTMA FLANGED SHORT SIGHT FLOW INDICATOR



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 07:06 PM

SKU
: 5235

BRAND
: DIXON VALVE

MODEL
: 5200-SFI-3

Use:
Allows for visual identification of fuel grade prior to opening the valve
Works with tank truck flanged butterfly valves found on gasoline trucks

Construction:
Durable cast aluminum housing
Acrylic sight glass
Baylast™ O-ring and retainer ring
Low cost sight glass tube can be easily replaced

Safety notes:
Due to the proprietary blending of petroleum products, Dixon recommends that the thermoplastic tubing and the gaskets be immersion tested in the product to be handled to ensure compatibility
Not compatible with crude oil.
Maximum flange bolt torque is 200 in-lb (inch pounds)
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Flange Size	3" TTMA
Fuel Compatability	Gasoline and diesel, up to E100 and B100 biofuels
ID	3-1/2"
Material	Aluminum
Factory Part Number	5200-SFI-3
Seal	Baylast?
Weight Lb	1.1800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Width	1-3/4"

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us