
API LOAD/UNLOAD VALVE







** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 05:07 PM

SKU
: 5270

BRAND
: DIXON VALVE

MODEL
: 5204NG

Applications:
Used for bottom loading and unloading of petroleum tankers, Load/unload valve permits both terminal loading, and fuel unloading through the valve.

Specifications:
Manufactured to American Petroleum Institute standard API RP-1004, which allows for positive connection to drop adapters and rack couplers such as the Dixon Bayco 5300/5400 series rack coupler.

Features:
Ergonomically curved handle operates on a short 62° degree stroke
Any required maintenance is simplified, Dixon Bayco API Valves can be completely rebuilt without the need to remove the valve from the tanker
Nose ring is anodized hard coat aluminum, which in most applications will provide years of trouble free service. Nose ring can be rotated to provide a fresh connection service.

Construction:
Aluminum body with anodized hard coat aluminum nose ring and stainless steel hardware
Fixed aluminum handle
Baylast™ seals

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Fuel Compatability	Gasoline and diesel, and up to E100 and B100 biofuels
Length	7"
Material	Aluminum
Factory Part Number	5204NG
Seal	Baylast?
Style	Fixed handle (no sight glass)
Weight Lb	11.7000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us