# DQC HS-SERIES ISO-B STEAM INTERCHANGE FEMALE COUPLER






** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:18 PM

SKU
: 22876

BRAND
: DIXON VALVE

MODEL
: 6HSF6-S

Applications:
Designed exclusively for steam applications

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Coupler has a large plated steel sleeve designed for easy gripping with gloves
Steel componentry is plated using ROHS Compliant Trivalent Chrome.
EPDM steam-grade seals are standard
Couplers have a redundant O-Ring sealing system (Dual O-rings with PTFE back-up)
Valve seals are crimped in place to maintain integrity during excessive flow conditions.
Special high-temp EPDM O-rings designed for steam service

Compatibility & Interchange Data:
Interchangeable to ISO7241 Series 'B'
Parker 60-Series Steam Couplings

Safety notes:
Maximum working pressure has been calculated using standard saturated steam at 194°C (382°F) for general purpose continuous service. For advanced operating pressure or super-heated steam applications, contact Dixon for further information.
Warning: Do not disconnect under pressure!
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Body Size** | 3/4" |
| **Factory Part Number** | 6HSF6-S |
| **Hex** | 1-5/16" |
| **Length** | 3.55" (90.2mm) |
| **Material** | 303 Stainless Steel |
| **Maximum OD** | 2.48" (63.0mm) |
| **Pressure Rating** | Rated to 200 PSI gauge saturated steam 382°F (194°C) |
| **Temperature Range** | -70°F to +400°F (-57°C to +204°C) |
| **Thread** | Female NPTF |
| **Thread Size** | 3/4"-14 |
| **Weight Lb** | 1.3600 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us