PUSH-IN MALE SWIVEL RUN TEE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:41 PM

SKU
: 6313

BRAND
: DIXON VALVE

MODEL
: 71S8X8

Use:
Suitable for vacuum service
Working pressure: suitable for use up to the maximum working pressure of the plastic tubing used.

Features:
Positive seal: no leaks, after tubing is inserted, seal is made
Secure tube retention: pulling on tubing only serves to tighten the connection
Full flow design provides up to 60% more flow than conventional fittings with internal tube supports.
Pre-applied PTFE based pipe sealant on all male pipe threads saves customer additional labor.

Installation
Saves up to 75% of assembly time versus the standard compression fittings.
Quick connect: simply push tubing in, no tools required.
Quick disconnect: hold two fingers on insert and pull tubing out, no tools required.
Reusable: connect and disconnect numerous times

Safety notes:
Fittings are suitable for use up to the maximum working pressure of the plastic tubing used
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	71S8X8
Male Thread	NPTF
Male Thread Size	1/4"
Material	Forged Brass
Temperature Range	-10°F to 200°F (-23°C to 93°C)
Tube OD	1/4"
Weight Lb	0.1125

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us