AIR BRAKE MALE BRANCH TEE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:54 PM

SKU
: 6326

BRAND
: DIXON VALVE

MODEL
: 72NAB62VS

Applications:
Designed for use in air brake systems or cab controls

Use:
Utilize ribbed sleeve for compression and positive grip
Compatible tubing: SAE J844 type A and B

Specifications:
Meets D.O.T FMVSS 571.106 and SAE J246
Ref. SAE 100425 BA

Features:
Positive grip

Construction:
Machined from CA260, CA345 or CA377 brass
Pre-applied thread sealant
Thread sealant may be white or burnt orange

Installation
Cut tubing squarely- maximum of 15° angle allowable.
Check that port or mating part is clean and free of debris.
Insert tubing into fittings until it bottoms on seat.
Tighten nut with wrench until one thread remains visible on the fittings body; (this will allow for a number of remakes) or, the nut should be screwed down finger tight, then wrench-tightened according to the tube size used.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	72NAB62VS
Flow	.217"
Material	Brass
Temperature Range	-40°F to 200°F (-40°C to 93°C)
Thread	Straight x Pipe
Thread Size	17/32"-24 x 1/8"
Tube Size	3/8"
Weight Lb	0.1130
Working Pressure	150 PSI

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us