LEGRIS THREADED IN-LINE FLOW CONTROL VALVE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:48 PM

SKU
: 6405

BRAND
: DIXON VALVE

MODEL
: 77751414

Applications:
Intake air flows freely through the flow control; exhaust air is metered out through a specially designed adjustment screw.

Use:
Working fluid: compressed air
May be installed as meter in or meter out devices

Features:
Unidirectional flow control valve
Arrow on the body of the valve indicates the direction of controlled flow

Construction:
Body: Nylon with nickel-plated brass thread
Adjustment Screw: Nickel-plated brass
Locking Nut: Nickel-plated brass
Threads: Nickel-plated brass

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	77751414
Female Thread	NPT
Female Thread Size	1/4"
Material	Nylon/Brass
Pressure Range	15 PSI to 145 PSI
Temperature Range	32°F to 158°F (0°C to 70°C)
Weight Lb	0.1900

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us