# DQC E-SERIES STRAIGHT THROUGH INTERCHANGE MALE COUPLER






** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 08:31 PM

SKU
: 6563

BRAND
: DIXON VALVE

MODEL
: 8EM8-B

Features:
Straight-Through Pressure-Wash Interchange
Interchanges with Parker ST, Foster FST, Hansen ST, and Tomco ST couplings
These couplers have no internal valves, providing maximum flow with minimum pressure drop.

Construction:
Machined components are manufactured using solid brass
Stainless steel balls, retaining rings and spring maximize corrosion resistance and extend service life.
Nitrile (Buna-N) seals are standard

Available Options:
Contact Dixon® for additional seal material options, pressure ratings and other technical information.

Safety notes:
Do Not Disconnect with pressure in line.
Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

## TECHNICAL SPECIFICATIONS

| | |
|---|---|
| **Body Size** | 1" |
| **Burst Pressure** | 4,800 PSI (331 Bar) |
| **Factory Part Number** | 8EM8-B |
| **Male Thread** | NPTF |
| **Male Thread Size** | 1" - 11-1/2 |
| **Material** | Brass |
| **Maximum Operating Pressure** | 1,200 PSI (83 Bar) |
| **Temperature Range** | -40°F - +250°F (-40°C - +121°C) |
| **Weight Lb** | 0.8900 |



KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us