GRAVITY UTILITY NOZZLE



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 05:53 PM

SKU
: 6642

BRAND
: DIXON VALVE

MODEL
: 900B34

Applications:
These delivery nozzles are ideally suited for low pressure use such as agricultural and 12 volt truck utility pumps, or gravity flow fittings in economy applications

Features:
Nozzles are manual operation, they do not have an automatic flow shut off.
Rugged design
Good flow rating

Construction:
Die cast zinc aluminum body
Plated steel trigger
Buna seals
Aluminum spout
Steel reducer bushing

Note:
Nozzles with a 3/4" female NPT inlet, use a 1" x 3/4" steel reducer bushing to achieve 3/4" female NPT inlet (included)
All fuel contains additives, which can vary by fuel brand and season. Please contact Dixon with a list of all additives and we will advise of any known compatibility issues.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Flow	95 GPM at 20 PSI
Inlet	3/4" female NPT
Material	Die cast zinc aluminum
Maximum Operating Pressure	25 PSI
Outlet	3/4" Bent Spout
Factory Part Number	900B34
Weight Lb	2.0300

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us