
A-SERIES PNEUMATIC FEMALE THREADED PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 06:06 PM

SKU
: 6769

BRAND
: DIXON VALVE

MODEL
: A2F2

Applications:
A series couplers are intended for use in compressed air service where the convenience of one hand operation and a compact profile is desired.

Specifications:
Rated pressure for connected Brass Coupler & Steel Plug: 1,000 PSI (70 bar)
Maximum Working and 8,000 PSI (550 bar) Burst

Construction:
Machined components are manufactured using solid bar stock.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
Proprietary Astronautics

Safety notes:
Pressure rating given at ambient temperature 70°F (21°C).
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Factory Part Number	A2F2
Hex	11/16"
Length	1.56"
Material	Steel
Maximum OD	0.79"
Pressure Rating	See Product Details

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Thread	NPTF
Thread Size	1/4"
Weight Lb	0.0700

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us