A-SERIES PNEUMATIC MALE THREADED PLUG

DATE
: 11/23/2026 06:38 PM

SKU
: 6772

BRAND
: DIXON VALVE

MODEL
: A2M2-B





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
A series couplers are intended for use in compressed air service where the convenience of one hand operation and a compact profile is desired.

Specifications:
Rated pressure for connected Brass Coupler & Brass Plug: 500 PSI (35 bar) Maximum Working and 6,500 PSI (450 bar) Burst

Construction:
Machined components are manufactured using solid bar stock.

Compatibility & Interchange Data:
Proprietary Astronautics

Safety notes:
Pressure rating given at ambient temperature 70°F (21°C).
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Factory Part Number	A2M2-B
Flow	25 CFM at 100 PSI
Hex	9/16"
Length	1.59"
Material	Brass
Maximum OD	0.65"
Pressure Rating	See Product Details

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Thread	NPTF
Thread Size	1/4"
Weight Lb	0.0500

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us