TRUESEAL? CHECK VALVE

DATE
: 11/23/2026 09:29 PM

SKU
: 6798

BRAND
: DIXON VALVE

MODEL
: A4VC4-MG



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Push-to connect check valves ensure protection against reversal of flow. The valves have an arrow molded into the body to indicate the direction of flow. Valves are designed for connection with either thermoplastic or soft metal tubing and are intended for use with liquids only.

Specifications:
NSF-51 listed

Construction:
Body Material: Acetal
O-ring: EPDM
Metal Grip Edge: 300 stainless steel

Safety notes:
Intended for use with liquids only
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Cracking Presure	1/3 PSI
Factory Part Number	A4VC4-MG
Material	Acetal
Maximum Operating Pressure	150 PSI (dependent on tubing used)
Seal	EPDM
Temperature Range	34°F to 150°F (1°C to 65°C)
Tube OD	1/4"
Weight Lb	0.0200

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us