BOSS-LOCK CAM & GROOVE TYPE D COUPLER X FEMALE NPT



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 11:25 PM

SKU
: 23059

BRAND
: DIXON VALVE

MODEL
: AD500

Applications:
Designed for use with liquids, consult Dixon for specific recommendations

Specifications:
No standard exists for the 5" fittings, and generally does not interchange with other manufacturers.

Construction:
Buna-N gasket
Boss-Lock cam arms
Supplied with pull-ring safety clips

Available Options:
Other gasket types are available, contact Dixon.

How it works:
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.
The cast-in lugs allow safety clips to be attached once the lugs are passed through slots in the special cam lever arms providing a positive locking action.
The pull ring safety clip simplifies the locking action on Boss-Lock couplers. No more inserting clips or dangling lanyards, just a twist and it's locked, giving you a low profile positive locking action.

Safety notes:
Under no circumstances should cam and groove couplings be used for compressed air or steam service!
Pressure rating recommendations are based on the use of mating Dixon fittings at ambient temperature 70°F (21°C) with a standard seal installed. For

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

use at elevated temperature or other unusual operating conditions, consult Dixon.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	AD500
Material	356T6 Aluminum
Maximum Operating Pressure	75 PSI
Seal	Buna-N
Size	5"
Weight Lb	3.5200

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us