AG-SERIES AGRICULTURAL BALL VALVE FEMALE THREADED PLUG





** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/24/2026 12:11 AM

SKU
: 6954

BRAND
: DIXON VALVE

MODEL
: AG4F4

Construction:
Machined components are manufactured using solid bar stock
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
Pioneer Agricultural Interchange
Parker/Pioneer 4000 Series, Faster NS/NV Series
Safeway Series-S20, Stucchi IR-Series

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	16500 PSI (1100 Bar)
Factory Part Number	AG4F4
Hex	1-1/16"
Length	1.95" (49.5mm)
Material	Steel
Maximum OD	1.21" (30.7mm)
Maximum Operating Pressure	4000 PSI (275 Bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female NPTF

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us

www.kmxusa.us

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

Weight Lb	0.2000

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us