
ANSI SPLIT FLANGE- SERIES SF



** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

DATE
: 11/23/2026 10:53 PM

SKU
: 23073

BRAND
: DIXON VALVE

MODEL
: ANSI20

Applications:
Provides a direct connection between a grooved adapter and an ANSI Class 125 and 150 raised face flanged component.

Use:
Can be used with flat face flanges by removing the raised projections on the outside face of the flange

Specifications:
Underwriters Listed
Factory Mutual approved
Bolts: 4
Bolt Size: 5/8"
Bolt Length: 5/8"

Features:
Comparable to Victaulic's #741 and Grinnell's #7012

Construction:
Rust inhibiting paint
EPDM gasket

Available Options:
Buna gaskets are available upon request, contact Dixon.

Safety notes:
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Factory Part Number	ANSI20
Material	Ductile Iron
Maximum Operating Pressure	300 PSI at 70°F(21°C)
Nominal Size	2"
Pipe OD	2.375"
Weight Lb	3.6000

KMX

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU

sales@kmxusa.us

www.kmxusa.us