WILKERSON FRL'S B18 COMPACT FILTER/REGULATOR



DATE
: 11/24/2026 08:20 PM

SKU
: 26056

BRAND
: DIXON VALVE

MODEL
: B18-03AG

** Referential image*
*** Some features may vary without prior notice. Sale subject to inventory availability*

Applications:
Over-under units are space savers and provide for installation in tight areas.
One common inlet/outlet for both filter and regulator saves on piping costs.

Use:
To increase regulated pressure, pull adjusting knob and turn clockwise. To reduce pressure, turn knob counter clockwise. To lock knob, push down.
Two 1/4" gauge ports located on the front and rear faces of the body. These ports may be used as additional regulated ports or for pressure gauges. Plug unused port(s).

Features:
5- 125 PSIG adjusting range for transparent bowl with guard
5 micron element
1.72 oz. bowl
Self-relieving standard
Spring-loaded diaphragm
Transparent Bowl supplied with GC230 gauge

Safety notes:
Designed for air service only!
SCFM ratings at 100 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us

TECHNICAL SPECIFICATIONS

Description	Automatic Drain, Transparent Bowl and Guard
Factory Part Number	B18-03AG
Flow	158 SCFM
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	150 PSIG (10.3 Bar)
Port	3/8"
Temperature Range	32°F to 125°F (0°C to 52°C)
Weight Lb	1.6800

KMX
2645 Executive Park Drive, Weston, Fort Lauderdale, FL 33331, EEUU
sales@kmxusa.us
www.kmxusa.us